



GAMITA PAK-IT PTE. LTD.

164 Kallang Way, #02-07 Kolam Ayer Industrial Estate
Singapore 349248
Homepage: <http://www.gamitapakit.com.sg>
Phone: +65 6842 2686 / +65 6846 0737 Fax: +65 6842 3698



Shrink Fast - 998

Shrinkfast® Model 998 is the leading heat tool for both shrink-wrapping and shrink-film processing. When time is of the essence, the power of the 998 will get the job done right – quickly and efficiently.



Powerful

Offering 15% more power than it's competitors, the model 998 will shrink the toughest jobs more quickly and economically. With 212,000 BTU's of power, a person can shrink-wrap a 40" x 48" x 60" pallet in less than 2 minutes.

Lightweight

With its sleek design and weighing only 2.2 lbs., the 998 is perfectly balanced for operator comfort. The 998's ergonomic design and fan shaped combustor lead to an even and steady heat pattern for consistent shrink-wrapping.

Safe

With it UL™ listing, the 998 is designed to handle the toughest industrial jobs with several built-in safety mechanisms: A "dead man" trigger is designed to automatically shut off the flame once the trigger is released. Also the Shrinkfast® patented combustion cycle allows the flame to burn outside the nozzle, which remains cool to the touch, even after extensive use. In addition, the regulator has an automatic safety POL that shuts off the propane supply in the case the hose gets cut or develops a leak.

Flexible

When shrink-wrapping large equipment or difficult to reach areas, the Shrinkfast® integrated extension system provides unlimited shrinking possibilities. With a 2', 4', or 6' extension available, no job is too big for the model 998.

Durable

The 998 comes with a full 1-year manufacturer's warranty on all parts and labor. Shrinkfast® also offers a full service repair facility that can answer any technical question and rebuild any Shrinkfast® heat tool or extension.

Versatile

Shrink-wrapping results in a five-sided protection from the elements. Shrink film also produces a stronger bond than either stretch-wrap or banding. This additional protection is critical during the transportation and storage of everything from those odd-shaped pallets to large industrial equipment.



Photo courtesy of De Shrink, Inc.




Photo courtesy of Pro-tek Plastics & Supply, Inc.



Photo courtesy of Shrinkwrap International, Inc.



Photo courtesy of Buffalo Shrink Wrap, Inc.

The Shrinkfast® Integrated Extension System



Lengths & Weights (weight includes heat tool)

- 2' - 4 lbs
- 4' - 5 lbs
- 6' - 6 lbs
- Quick push button disconnect/connect
- Standard Arm Assist Clip for shrinking large jobs and "one handed operation"
- 75 degree angle of combustor for shrinking curved surfaces