



### **3510VA**

#### **Vacuum Sealer**

Comes standard with retractable stainless steel nozzles system for easier packaging and sustained vacuum flow

Pump inclusive inside

Available in 5mm and 10mm sealing widths

### **605VAD / VGD**

#### **Bi-Active Vacuum Sealer / Gas Flush**

It can seal up to 0.6mm gusseted or regular thermoplastic film

Ideal for aluminium foil coated bags and gusset bags

Available in 5mm and 10mm sealing widths

### **455VG / VGD**

#### **Vacuum and gas flush sealer**

\*Require air compressor

Available in 5mm and 10mm sealing widths

<b>Model</b>	<b>Sealing Length</b>	<b>Max Seal Thickness</b>	<b>Seal Width</b>	<b>Watts</b>	<b>Weight</b>
455 VG/VA	450 mm	2 x 0.15 mm	5 mm	1100 W	23 KG
4510 VG/VA	450 mm	2 x 0.15 mm	10 mm	1500 W	28 KG
605 VG/VA	600 mm	2 x 0.15 mm	5 mm	1400 W	29 KG
6010 VG/VA	600 mm	2 x 0.15 mm	10 mm	1500 W	30 KG
455 VGD/VAD	450 mm	2 x 0.4 mm	5 mm	1800 W	21 KG
4510 VGD/VAD	450 mm	2 x 0.4 mm	10 mm	2400 W	27KG
605 VGD/VAD	600 mm	2 x 0.4 mm	5 mm	2200 W	30 KG
6010 VGD/VAD	600 mm	2 x 0.4 mm	10 mm	2800 W	31 KG
355 VG/VA	350 mm	2 x 0.15 mm	5 mm	1000 W	27 KG
3510 VG/VA	350 mm	2 x 0.15 mm	10 mm	1200 W	29 KG